

Method for developing photographic silver halide recording materials.

Method for developing photographic silver halide recording materials.

Patent Number: ☐ EP0429973
Publication date: 1991-06-05
Inventor(s): KIESSLICH GUENTER DR (DE); WADEWITZ GUENTER (DE)
Applicant(s): DU PONT DEUTSCHLAND (DE)
Requested Patent: ☒ DE3938573
Application Number: EP19900121873 19901115
Priority Number(s): DE19893938573 19891121
IPC Classification: G03C1/38; G03C5/305
EC Classification: G03C1/38F, G03C5/305B
EC Classification: G03C1/38F; G03C5/305B
Equivalents: CA2029945, ☐ JP3211546
Cited Documents: US3754924; US2000353; US4840881; US4859567

Abstract

If photographic silver halide materials which contain nonionic fluorinated surface-active substances are developed in developers rich in hydroquinone and sulphite, the recorded image is spoilt by white spots. This defect disappears if a wetting agent is dissolved in a quantity of at least 0.1 g/l in the developer. The invention can be used in the production of images by means of silver halide materials, especially in medical diagnostics and in reprography.

Data supplied from the **esp@cenet** database - I2

Color developing solution for light-sensitive silver halide color photographic material and processing method

Color developing solution for light-sensitive silver halide color photographic material and processing method

Patent Number: EP0436947
Publication date: 1991-07-17
Inventor(s): UEDA YUTAKA C O KONICA CORPORA (JP); KOBOSHI SHIGEHARU C O KONICA C (JP)
Applicant(s): KONISHIROKU PHOTO IND (JP)
Requested Patent: ☒ EP0436947, B1
Application Number: EP19900125712 19901228
Priority Number(s): JP19900158057 19900615; JP19890341357 19891228
IPC Classification: G03C7/413
EC Classification: G03C7/413
EC Classification: G03C7/413
Equivalents: DE69031026D, DE69031026T, JP2915095B2, ☐ JP3223757
Cited Documents: US4232112; EP0312984; EP0273986; GB669505; FR1080765; US3996054; GB1094826; JP55018675; JP62056961

Abstract

There are disclosed a color developing solution for a light-sensitive silver halide color photographic material which comprises a sulfite concentration of 1.0×10^{-3} mole or lower per liter of the color developing solution and containing 0.5 to 20 g/l of a water-soluble surfactant and a processing method using the color developing solution.